

Model RE 53



Oven with gravity convection for all standard drying and tempering tasks as well as sterilizing or preheating of glassware.

EQUIPMENT:

Microprocessor controller with digital display of the temperature in °C

Temperature setting with one degree sensitivity

Build-in timer can be set to 0-9999 minutes or continuous operation

Pre-set high temperature limit safety thermostat class 1

Exhaust duct (Ø 50mm) at rear of unit with manually adjustable slide

Stainless steel interior equipped with 2 chrome-plated shelves (4 shelves max)(1)

2 units are directly stackable using the flat assembly bars supplied with the units

TECHNICAL SPECIFICATION:

Size (liter):	53
Temperature Range (°C):	7 above ambient to 220
Uniformity at 150 °C (± K):	± 3.6
Fluctuation at 150 °C (± K):	± 0.4
Heating up time at 150 °C (min):	45
Recovery time at 150 °C (min):	18
Nominal Voltage 50/60 Hz (V):	230 V-CE certificate version / Plug: EU
Nominal Power (W):	800

EXTERIOR DIMENSIONS: (II)

Width / Height / Depth (mm):	600 / 680 / 620
-------------------------------------	-----------------

INTERIOR DIMENSIONS: (II)

Width / Height / Depth (mm):	400 / 400 / 330
Weight incl. 2 shelves (kg):	41
Dimensions unit incl. packaging Width / Height / Depth (mm):	730 / 800 / 760
Total weight incl. packaging (kg):	approx. 48



Made and designed in Germany

Dimensions refer to unit housing including unit feet, door hinges, vent cover. Please note: Technical specifications refer to 25 °C ambient temperature, 150 °C set temperature and voltage fluctuation of ±10%. The temperature data are determined in following to DIN12880. Technical data are based on 230Volt.