

Model RF 115



Drying oven with force convection for all standard drying and tempering tasks as well as sterilizing glassware, when shorter drying times are desired.

EQUIPMENT:

- Microprocessor controller with digital display of the temperature in °C
- Temperature setting with one degree sensitivity
- Build-in timer can be set to 0-9999 minutes or continuous operation
- Pre-set high temperature limit safety thermostat class 1
- Exhaust duct (Ø 50mm) at rear of unit with manually adjustable slide
- Stainless steel interior equipped with 2 chrome-plated shelves (4 shelves max)(1)
- 2 units are directly stackable using the flat assembly bars supplied with the units

TECHNICAL SPECIFICATION:

Size (liter):	115
Temperature Range (°C):	7 above ambient to 220
Uniformity at 150 °C (± K):	± 3.0
Fluctuation at 150 °C (± K):	± 0.3
Heating up time at 150 °C (min):	36
Recovery time at 150 °C (min):	20
Nominal Voltage 50/60 Hz (V):	230 V-CE certificate version / Plug: EU
Nominal Power (W):	1000

EXTERIOR DIMENSIONS: (II)

Width / Height / Depth (mm):	800 / 760 / 660
------------------------------	-----------------

INTERIOR DIMENSIONS: (II)

Width / Height / Depth (mm):	600 / 480 / 400
Weight incl. 2 shelves (kg):	63
Dimensions unit incl. packaging Width / Height / Depth (mm):	930 / 1000 / 810
Total weight incl. packaging (kg):	approx. 78



Made and designed in Germany

Dimensions refer to unit housing including unit feet, door hinges, vent cover. Please note: Technical specifications refer to 25 °C ambient temperature, 150 °C set temperature and voltage fluctuation of ±10%. The temperature data are determined in following to DIN12880. Technical data are based on 230Volt.