

# Universal oven Model UF30



# Standard equipment

#### **Ventilation and Control**

- forced air circulation by quiet air turbine, adjustable in 10% steps
- adjustment of pre-heated fresh air admixture by air flap control in 10% steps
- · vent connection with restrictor flap
- adaptive multifunctional digital PIDmicroprocessor controller with high-definition TFT-colour display
- · self-diagnostics for fault analysis
- 1 Pt100 sensor DIN class A in 4-wire-circuit
- digital timer adjustable from 1 minute to 99 days, 23 hours
- parameters adjustable on ControlCOCKPIT: temperature (Celsius or Fahrenheit), fan speed, air flap position, programme time, time zones, summertime/wintertime
- SetpointWAIT function the process time does not start until the set temperature is reached
- resolution of display for setpoint values 0.1 °C up to 99.9 °C, 0.5 °C from 100 °C and for actual values 0.1 °C (LED)
- calibration facility directly at ControlCOCKPIT for three freely selectable temperature values
- programme stored in case of power failure
- incl. works calibration certificate for +160 ℃

## Overtemperature protection (double)

 adjustable electronic overtemperature monitor and mechanical temperature limiter TB, protection class 1 according to DIN 12 880 to switch off the heating approx. 20 ℃ above nominal temperature

#### **Textured Stainless Steel Casing**

- w x h x d: 585 x 707 x 434 mm
- fully insulated stainless steel door with 2-point locking (compression door lock)
- rear zinc-plated steel

### **Interior - Heating Concept**

- w x h x d: 400 x 320 x 250 mm, 32 l
- easy-to-clean interior,made of stainless steel,reinforced by deep drawn ribbing with integrated and protected large-area heating on four sides
- 1 stainless steel grid

# Temperature Range

min.10 °C above ambient up to +300 °C

## **Voltage / Power Rating**

- 230 V (+/- 10%), 50/60 Hz
- ca. 1.600 W

## **Packing Data**

- net weight approx. 44 kg
- · gross weight carton approx. 55 kg
- dimensions approx.: carton w x h x d: 69 x 96 x 66 cm
- the appliances must be transported upright

# **Customs Tariff Number**

8419 8998

## **Country of Origin**

Federal Republic of Germany

# WEEE-Reg.-No.

• DE 66812464